

## 5000UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information  
please call

1-800-Belden1

**General Description:**

Security & Commercial Audio Cable, Riser-CL3R-FPLR 2-12 AWG stranded bare copper conductors with polyolefin insulation, PVC jacket with ripcord

**Usage (Overall)**

Suitable Applications: Intercom/PA Systems, Sound/Audio Systems, Fire Alarm (For color Red only)(Dual Rated)

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 2            | 12  | 19x25     | BC - Bare Copper   |

Total Number of Conductors: 2

**Insulation**

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|---------------------|----------------------|
| PP - Polypropylene  | 0.011                |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | 0.017                     |

Outer Jacket Ripcord: Yes

**Overall Cable**

Overall Cabling Lay Length & Direction:

| Length (in.) | Direction | Twists (twist/ft) |
|--------------|-----------|-------------------|
| 4.500        | Left Hand | 2.700             |

Overall Cabling Color Code Chart:

| Number | Color |
|--------|-------|
| 1      | Black |
| 2      | White |

Overall Nominal Diameter: 0.260 in.

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 53.600 lbs/1000 ft.

Max. Recommended Pulling Tension: 152 lbs.

Min. Bend Radius/Minor Axis: 2.625 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC(UL) Specification: CL3R, FPLR

NEC Articles: 725 or 760

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

## 5000UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

|                                       |            |
|---------------------------------------|------------|
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |
| EU Directive 2003/11/EC (BFR):        | Yes        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes        |
| MII Order #39 (China RoHS):           | Yes        |

## Flame Test

|                 |                       |
|-----------------|-----------------------|
| UL Flame Test:  | UL1666 Vertical Riser |
| CSA Flame Test: | FT4                   |

## Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

## Plenum/Non-Plenum

|                |        |
|----------------|--------|
| Plenum (Y/N):  | No     |
| Plenum Number: | 6000UE |

## Electrical Characteristics (Overall)

## Nom. Inductance:

Inductance (μH/ft)

0.15

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

24.000

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

1.6

## Max. Operating Voltage - UL:

Voltage

300 V RMS

## Max. Recommended Current:

| Description          | Current                              |
|----------------------|--------------------------------------|
| 10C Temperature Rise | 12 Amps per conductor @ 25°C ambient |

## Put Ups and Colors:

| Item #         | Putup    | Ship Weight | Color | Notes | Item Desc      |
|----------------|----------|-------------|-------|-------|----------------|
| 5000UE 0021000 | 1,000 FT | 54.000 LB   | RED   | C     | 2 #12 PP FRPVC |
| 5000UE 0081000 | 1,000 FT | 54.000 LB   | GRAY  | C     | 2 #12 PP FRPVC |
| 5000UE 008500  | 500 FT   | 27.000 LB   | GRAY  | C     | 2 #12 PP FRPVC |
| 5000UE 0101000 | 1,000 FT | 54.000 LB   | BLACK | C     | 2 #12 PP FRPVC |

## Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-09-2013

© 2016 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).